




# AQUALINE®


## PERMEABLE PAVER

LOW MAINTENANCE AND PROVEN DURABILITY THAT ALLOWS FOR FLEXIBLE DESIGN OPTIONS

### PALLET LAYOUT



Stacked Bond Pallet Layout



90° Herringbone Pallet Layout

### FEATURES & BENEFITS

- Can eliminate stormwater runoff and improve water quality
- Meets the requirements of CSA A231.2
- Interlocking spacer bars for increased structural performance
- Smooth surface texture with a micro-chamfer to minimize vibration and enhance wheelchair comfort
- Can be utilized to construct an ADA-compliant pavement
- True installed dimensions for design optimization
- Optimal joint openings for infiltration and maintenance
- Chamfer Width: 3 mm
- Spacer Bar Width: 7 mm
- Surface Infiltration Rate: > 500 inches per hour (varies based on joint infill gradation)
- Surface Open Area: 7%

### SHAPES & SIZES


#### PAVER




4.5" x 9" x 31/8"  
114 x 230 x 80 mm

 ENVIRONMENTAL COLLECTION


### LAYING PATTERNS



RUNNING BOND



HERRINGBONE

Mechanical Installation Available 

Contact your local Belgard® representative for details and mechanical availability.

Belgard permeable pavers can be used for a variety of different vehicular applications. Appropriate shape and thickness is based on project-specific conditions, including type of loading, base design, and subgrade conditions. It is recommended that you consult a Belgard Representative when specifying products for vehicular applications.

Check with your local Belgard Representative for product availability and colour options.



For more info, visit [BelgardCommercial.com](http://BelgardCommercial.com)

#### CANADA WEST

British Columbia Alberta Manitoba Saskatchewan

For the most current product offering and technical references – go to [www.BelgardCommercial.com](http://www.BelgardCommercial.com)



©2025 Oldcastle® APG, A CRH Company. All Rights Reserved. BEL 25-001 AQUALINE