

GENERAL NOTES: APPLY TO ALL OF THE BELOW PRODUCTS:

1. INSTALLATION MUST BE COMPLETED IN ACCORDANCE WITH MANUFACTURER SPECIFICATIONS.
2. DRAWINGS NOT TO SCALE.
3. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT: www.belgardcommercial.com
4. "ADHERE" - INSTALLER MUST ADHERE WITH POLYURETHANE CONSTRUCTION ADHESIVE.

ADD ADDITIONAL PEDESTALS AS NEEDED TO ADEQUATELY SUPPORT PAVERS

ADD EXTRA PEDESTALS UNDER TRIANGULAR SHAPE CUT PAVERS TO PREVENT ROCKING (TYP)

MAX. 1/8" GAP AT PERIMETER (TYP)

REMOVE EXTRA TABS ON PEDESTALS AROUND PERIMETER AS NEEDED (TYP)

SLOPE

CUT PEDESTAL BASES, ON CUT LINES (SEE BELOW), AS NEEDED TO FIT AROUND PERIMETER

PAVERS

REINSERT REMOVED TABS AND ADHERE IN BETWEEN PAVERS TO MAINTAIN SPACING (TYP)

RIDGE LINE

VALLEY LINE


PEDESTAL (TYP)

DIAGONAL PERIMETER PLACEMENT

ADHERE SMALL CUT PAVERS TO PEDESTAL(S)
 RE-INSERT REMOVED TABS AND ADHERE IN BETWEEN PAVERS TO MAINTAIN SPACING (TYP)

REMOVE EXTRA TABS ON PEDESTALS AROUND PERIMETER AS NEEDED (TYP)

TOP OF NEW DECK
 MAX. 1/8" GAP AT PERIMETER (TYP)
 TOP OF PEDESTAL




PAVER
 PEDESTAL (TYP)
 CAVITY HEIGHT
 CUT PEDESTAL BASE ALONG CUT LINES

SLOPE COMPENSATION
 ADHERE SHIMS UNDER CUT PEDESTAL FOR SLOPE COMPENSATION

DO NOT ADHERE TO SUBSTRATE

NARROW & SMALL CUT PAVER PERIMETER PLACEMENT



PEDESTAL BASE VIEW