



NOTE: FIP SPREADS DECK WEIGHT OVER A LARGER SURFACE AREA (12" X 12")



PEDESTALS ON FIBs (FLOATING INSULATION BASES)

NOTE: IN SEISMIC SDC ZONES D, E, & F, DRIVE TWO (2X) 3/8" DIAMETER X 8" LONG HOT GALVANIZED SPIKES INTO EACH CORNER OF THE FFB. SPIKES MUST BE DRIVEN A MINIMUM 7" INTO THE GROUND



PEDESTALS ON FFBs (FLOATING FOUNDATION BASES)

GENERAL NOTES: APPLY TO ALL OF THE ABOVE PRODUCTS:

1. INSTALLATION MUST BE COMPLETED IN ACCORDANCE WITH MANUFACTURER SPECIFICATIONS.
2. DRAWINGS NOT TO SCALE.
3. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT: www.belgardcommercial.com