




AQUA-BRIC[®] TYPE 4

PERMEABLE PAVER

IDEAL FOR HEAVY DUTY
VEHICULAR APPLICATIONS AND
MACHINE-INSTALLED PROJECTS


PALLET LAYOUT




FEATURES & BENEFITS

- Can eliminate stormwater runoff and improve water quality
- Meets the requirements of ASTM C936
- Smooth surface texture with a micro-chamfer to minimize vibration and enhance wheelchair comfort
- Can be utilized to construct an ADA-compliant pavement
- Innovative joint and void design optimizes structural performance
- False joint option (Type 4) provides a multi-size appearance
- Chamfer Width: 3 mm
- Joint Width: 5 mm
- Maintenance Void: 9 mm
- Surface Infiltration Rate: > 900 inches per hour (varies based on joint infill gradation)
- Surface Open Area: 9%


LAYING PATTERNS




BASKET WEAVE



HERRINGBONE PATTERN



RUNNING BOND PATTERN

Mechanical
Installation Available 

Contact your local Belgard[®] representative for details and mechanical availability.

Contact your local Belgard sales representative for available colors.

SHAPES & SIZES

AQUA-BRIC TYPE 4 (MECHANICAL)



5 x 10 x 3 1/8"

Pallet includes half pieces