



# BELAIR WALL 2.0

FREESTANDING AND  
RETAINING WALL

CHISELED STONE APPEARANCE  
FOR SOPHISTICATED LANDSCAPES

## ☑ FEATURES & BENEFITS

- Freestanding & gravity walls\* can be built up to 3 feet high, including buried course
- Taller walls can be built using geosynthetic reinforcement when designed by a qualified engineer
- Rear-lip on retaining wall block makes installation fast and accurate
- Freestanding Walls: 4-foot minimum radius using all 3 units
- Retaining Walls: 1 7/8" Setback/ System batter
- Minimum outside radius, measured on the top course to the front of the units: 4 feet
- Minimum inside radius, measured on the base course to the front of the units: 8 feet

## 🧱 SHAPES & SIZES\*\*

### SRW



6 x 6 x 8



6 x 10 x 8



6 x 16 x 8

### FSW



6 x 6 x 5



6 x 10 x 5



6 x 16 x 5

### COLUMN/CORNER



6 x 16 x 8

### TRAPEZOID DOUBLE-SIDED CAP



3 x 7/8 x 13 1/2

### CAP END 3-SIDED



3 x 8 x 13 1/2

### WALL END 3-SIDED



6 x 8 x 11

### U START BASE BLOCK®



3 1/2 x 18 1/2 x 12

\*Gravity wall heights are based on project specific conditions and may be lower than this value.  
Check with your local Belgard Representative for product availability and color options.



For more info, visit [BelgardCommercial.com](http://BelgardCommercial.com)

Oldcastle APG - A CRH Company  
400 Perimeter Center Terrace, Suite 1000  
Atlanta, GA 30346  
1-844-495-8210



© 2022 Oldcastle® APG, A CRH Company. All Rights Reserved.  
BEL20-202 Rev: 6/16/2022